

**INFORMACIJOS, TEIKIAMOS PAGAL LIETUVOS RESPUBLIKOS PINIGŲ
PLOVIMO IR TERORISTŲ FINANSAVIMO PREVENCIJOS ĮSTATYMO 17 STR.
1–3 D., TEIKIMO, KAI DUOMENYS PATEIKIAMI „SISTEMA-SISTEMA“ BŪDU,
FORMOS NR. F-3 FORMATU, WSDL SCHEMA**

1. Funkcijos ir jų parametrai

Duomenų teikėjų kviečiama funkcija:

- acceptCTRData

| Funkcija | Parametrai | | Aprašymas |
|----------------------------|--|---|---|
| | Įėjimo | Išėjimo | |
| CTRDataService.wsdl | | | |
| acceptCTRData | ctrData: lt.fntt.exchange.model.ctr.CashTransactionReport | Funkcija nieko negrąžina, tačiau gali pateikti klaidą lt.fntt.exchange.services.ctr.CTRDataFault_Exception | Perduodamas dokumentas: CTR (angl. Cash Transaction Report) duomenys |

2. CTR duomenų surinkimo serviso WSDL aprašai

2.1. CTRDataService.wsdl

```
<?xml version='1.0' encoding='UTF-8'?><wSDL:definitions
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:wsu="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-utility-1.0.xsd" xmlns:wsp="http://www.w3.org/ns/ws-policy"
xmlns:wSDL="http://schemas.xmlsoap.org/wSDL/" xmlns:tNS="http://www.springframework.org/schema/beans"
xmlns:sp="http://docs.oasis-open.org/ws-sx/ws-securitypolicy/200702"
xmlns:soap="http://schemas.xmlsoap.org/wSDL/soap/" xmlns:ns2="http://schemas.xmlsoap.org/soap/http"
xmlns:ns1="urn:lt:fntt:exchange:services:ctr" name="ctrDataImporterService"
targetNamespace="http://www.springframework.org/schema/beans">
  <wSDL:import location="http://localhost:8181/cxf/CTRDataService?wSDL=CTRDataServiceTypes.wsdl"
namespace="urn:lt:fntt:exchange:services:ctr">
    </wSDL:import>
  <wSDL:binding name="ctrDataImporterServiceSoapBinding" type="ns1:CTRDataService">
    <wsp:PolicyReference URI="#UsernameAndDigestPasswordPolicy"/>
    <soap:binding style="document" transport="http://schemas.xmlsoap.org/soap/http"/>
    <wSDL:operation name="acceptCTRData">
      <soap:operation soapAction="" style="document"/>
      <wSDL:input name="acceptCTRData">
        <soap:body use="literal"/>
      </wSDL:input>
      <wSDL:output name="acceptCTRDataResponse">
        <soap:body use="literal"/>
      </wSDL:output>
      <wSDL:fault name="CTRDataFault_Exception">
        <soap:fault name="CTRDataFault_Exception" use="literal"/>
      </wSDL:fault>
    </wSDL:operation>
```

```

</wsdl:binding>
<wsdl:service name="ctrDataImporterService">
  <wsdl:port binding="tns:ctrDataImporterServiceSoapBinding" name="CTRDataServiceImplPort">
    <soap:address location="http://localhost:8181/cxf/CTRDataService"/>
  </wsdl:port>
</wsdl:service>
<wsp:Policy wsu:Id="UsernameAndDigestPasswordPolicy">
  <sp:SupportingTokens>
    <wsp:Policy>
      <sp:UsernameToken
        sp:IncludeToken="http://docs.oasis-open.org/ws-sx/ws-
securitypolicy/200702/IncludeToken/AlwaysToRecipient">
      <wsp:Policy>
        <sp:HashPassword/>
      </wsp:Policy>
    </sp:UsernameToken>
  </wsp:Policy>
</sp:SupportingTokens>
</wsp:Policy>
</wsdl:definitions>

```

3. CTRDataServiceTypes

```

<?xml version='1.0' encoding='UTF-8'?><wsdl:definitions
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
xmlns:ns1="urn:lt:fntt:exchange:services:ctr" name="CTRDataService"
targetNamespace="urn:lt:fntt:exchange:services:ctr">
  <wsdl:types>
    <xs:schema
      xmlns:xsd="http://www.w3.org/2001/XMLSchema"
      xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
      xmlns:tns="urn:lt:fntt:exchange:services:ctr"
      xmlns:ns1="urn:lt:fntt:exchange:model:ctr"
      targetNamespace="urn:lt:fntt:exchange:services:ctr" version="1.0">
      <xs:import
        namespace="urn:lt:fntt:exchange:model:ctr"
        schemaLocation="http://localhost:8181/cxf/CTRDataService?xsd=ctr_data_schema.xsd"/>
      <xs:element name="CTRDataFault" type="tns:CTRDataFault"/>
      <xs:element name="acceptCTRData" type="tns:acceptCTRData"/>
      <xs:element name="acceptCTRDataResponse" type="tns:acceptCTRDataResponse"/>
      <xs:complexType name="acceptCTRData">
        <xs:sequence>
          <xs:element minOccurs="0" name="ctrData" type="ns1:CashTransactionReport"/>
        </xs:sequence>
      </xs:complexType>
      <xs:complexType name="acceptCTRDataResponse">
        <xs:sequence/>
      </xs:complexType>
      <xs:complexType name="CTRDataFault">
        <xs:sequence>
          <xs:element maxOccurs="unbounded" minOccurs="0" name="classContext" nillable="true"
type="xs:string"/>
          <xs:element minOccurs="0" name="code" type="xs:string"/>
          <xs:element minOccurs="0" name="message" type="xs:string"/>
        </xs:sequence>
      </xs:complexType>
    </xs:schema>
  </wsdl:types>
  <wsdl:message name="acceptCTRDataResponse">
    <wsdl:part element="ns1:acceptCTRDataResponse" name="parameters">
  </wsdl:part>
</wsdl:message>
<wsdl:message name="acceptCTRData">
  <wsdl:part element="ns1:acceptCTRData" name="parameters">
</wsdl:part>

```

```
</wsdl:message>
<wsdl:message name="CTRDataFault_Exception">
  <wsdl:part element="ns1:CTRDataFault" name="CTRDataFault_Exception">
  </wsdl:part>
</wsdl:message>
<wsdl:portType name="CTRDataService">
  <wsdl:operation name="acceptCTRData">
    <wsdl:input message="ns1:acceptCTRData" name="acceptCTRData">
    </wsdl:input>
    <wsdl:output message="ns1:acceptCTRDataResponse" name="acceptCTRDataResponse">
    </wsdl:output>
    <wsdl:fault message="ns1:CTRDataFault_Exception" name="CTRDataFault_Exception">
    </wsdl:fault>
  </wsdl:operation>
</wsdl:portType>
</wsdl:definitions>
```
